

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
1 February 2001 (01.02.2001)

PCT

(10) International Publication Number
WO 01/08224 A1

- (51) International Patent Classification⁷: H01L 27/146, G01T 1/24
- (21) International Application Number: PCT/IL99/00409
- (22) International Filing Date: 26 July 1999 (26.07.1999)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **EDGE MEDICAL DEVICES LTD.** [IL/IL]; 25 Hatasiya Street, North Industrial Zone, 43654 Raanana (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **ZUR, Albert** [IL/IL]; 49/7 Harei Yehuda Street, 55900 Ganei Tikva (IL).
- (74) Agents: **COLB, Sanford, T. et al.**; Sanford T. Colb & Co., P.O. Box 2273, 76122 Rehovot (IL).
- (81) Designated States (national): AE, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:
— With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DIGITAL DETECTOR FOR X-RAY IMAGING



(57) Abstract: The present invention discloses an X-ray imaging module having a multilayer ionizing radiation sensitive element (60) operative to convert spatially modulated impinging X-ray radiation to a spatially modulated charge distribution. The multilayer ionizing radiation sensitive element has a substrate (100), a conductive layer (102) overlying the substrate, an ionizing radiation sensitive layer (104) overlying the conductive layer which converts ionizing radiation impinging thereon to charge carriers, and a blocking layer (106) exposed to ionizing radiation and optical radiation, overlying the ionizing radiation sensitive layer. The blocking layer limits the passage of charges, of at least one polarity, and blocks optical radiation, of at least one spectral band, from penetrating therethrough, while permitting passage therethrough of ionizing radiation. The X-ray imaging module also contains a charge injection assembly (68) operative to inject charge into the multilayer ionizing radiation sensitive element and readout circuitry coupled to the multilayer ionizing radiation sensitive element.

WO 01/08224 A1